



ELECTRIC BOLT SERIES

The Trusted Name For Excellent Quality



EB206



Low Temperature

The ELEM fail safe electric bolt with adjustable feature

Face Plate: 205Lx35Wx40H(mm)
Strike: 100Lx25Wx3H(mm)
Bolt: 16mmDIA, stainless steel 16mm throw
Voltage: 12VDC, low power
Operation Current: 900mA
Stand by Current: 100mA
Fail-safe type
Weight: 0.8Kg

磁珠式电插锁

锁体尺寸: 长205x宽35x高40(mm)
吸板尺寸: 长100x宽25x高3(mm)
锁芯尺寸: 16mm(凸出长度)x16mm(直径)
工作电压: 12伏, 超低功耗
启动电流: 900mA
工作电流: 100mA
适用门式: 木门、玻璃门、金属门
开门方式: 双向开门; 可推拉
断电关门、断电开门
产品重量: 0.8kg

EB207



Low Temperature

The ELEM fail safe electric bolt with magnetic feature

Face Plate: 262Lx35Wx40H(mm)
Strike: 100Lx25Wx3H(mm)
Bolt: 16mmDIA, stainless steel 16mm throw
Voltage: 12VDC, low power
Operation Current: 900mA
Stand by Current: 150mA
Fail-safe type
Weight: 0.1Kg

定位型智能高保安电插锁

锁体尺寸: 长262x宽35x高40(mm)
吸板尺寸: 长100x宽25x高3(mm)
锁芯尺寸: 16mm(凸出长度)x16mm(直径)
工作电压: 12伏, 超低功耗
启动电流: 900mA
工作电流: 150mA
适用门式: 木门、玻璃门、金属门
开门方式: 双向开门; 可推拉
承受剪力: 1000kg冲击力
配备功能: 锁状态输出, 自动重复功能
断电关门、断电开门
产品重量: 0.1kg

EB208



Low Temperature

The ELEM fail secure electric Bolt with profile cylinder

Face Plate: 260Lx35Wx48H(mm)
Strike: 100Lx25Wx2.7H(mm)
Bolt: 16mmDIA, stainless steel 16mm throw
Voltage: 12VDC
Operation Current: 900mA
Stand by Current: 150mA
Time: 0.3, 6, 9sec.
Fail-secure type
Weight: 1.3Kg

坚固智能型电插锁

锁体尺寸: 长260x宽35x高48(mm)
吸板尺寸: 长100x宽25x高2.7(mm)
锁芯尺寸: 16mm(凸出长度)x16mm(直径)
工作电压: 12伏 (超低功耗)
启动电流: 900mA
工作电流: 150mA
适用门式: 木门、玻璃门、金属门
承受剪力: 1000kg冲击力
开门方式: 双向开门可推拉
附钥匙或外出旋钮
断电关门、通电开门
产品重量: 1.3kg

UBK200



The Electric bolt U bracket is suitable for frameless glass door.

U bracket and strike housing for fixing electric bolt strike plate to glass doors.
The electric bolt must be housed in a solid door header.

Suitable for: EB201/202/203/205/206
Glass thickness: 8-15mm
Weight: 0.3Kg

U型玻璃门电插锁专用支架

通用型号: EM201/202/203/205/206
适用门式: 无框玻璃门专用
选用材质: 不锈钢表面拉丝
开门方式: 180度双向开门
玻璃厚度: 8-15mm
产品重量: 0.3kg

EG939U



The ELEM fully stainless steel Bracket is suitable for Fully Frameless Glass Door Only

Size: 205Lx58Wx46H(mm)
Suitable for: EB201/202/203/206
Glass Thickness: 8-15mm
Weight: 1.57Kg

U型上下无框玻璃门专用支架

外形尺寸: 长205x宽58x高46(mm)
通用型号: EB201/202/203/206
选用材质: 不锈钢表面拉丝
玻璃厚度: 8-15mm
产品重量: 1.57kg



ELECTRIC STRIKE SERIES

The Trusted Name For Excellent Quality



ES123A/ES123B



The ELEM heavy duty electric strike is suitable for cylindrical locks, Available fail safe or fail secure.

Face Plate: 150Lx39.5Wx28H(mm)
Voltage: 12VDC(24dc by optional)
Current: 250mA
Feature: Fail Secure ES123A
Fail Secure ES123B
Weight: 0.36kg

重型短面板电锁口

锁体尺寸: 长124x宽43x高32(mm)
工作电压: 12伏(24伏可订)
适用门式: 木门、金属门
开门方式: 单向开门
ES123A 通电开门 断电关门
ES123B 通电关门 断电开门
颜色选择: 不锈钢面板、铝面板
产品重量: 0.36kg

ES123A-S/ES123B-S



The ELEM heavy duty electric strike is suitable for cylindrical locks, Available fail safe or fail secure.

Face Plate: 150Lx39.5Wx28H(mm)
Voltage: 12VDC(24dc by optional)
Current: 250mA
Feature: Fail Secure ES123A-S
Fail Secure ES123B-S
Signal output: Locksignal NO/NC/COM
Weight: 0.36kg

重型短面板电锁口附信号输出

锁体尺寸: 长124x宽43x高32(mm)
工作电压: 12伏 (24伏可订)
适用门式: 木门、金属门
信号接点: 锁信号输出NO、NC、COM
开门方式: 单向开门
ES123A-S 通电开门 断电关门
ES123B-S 通电关门 断电开门
颜色选择: 不锈钢面板、铝面板
产品重量: 0.36kg

ES123LA/ES123LB



The ELEM heavy duty electric strike is suitable for cylindrical locks, Available fail safe or fail secure.

Face Plate: 165Lx43Wx32H(mm)
Voltage: 12VDC(24dc by optional)
Current: 250mA
Feature: Fail Secure ES123LA
Fail Secure ES123LB
Weight: 0.36kg

重型长面板电锁口

锁体尺寸: 长165x宽43x高32(mm)
工作电压: 12伏 (24伏可订)
适用门式: 木门、金属门
开门方式: 单向开门
ES123LA 通电开门 断电关门
ES123LB 通电关门 断电开门
颜色选择: 不锈钢面板、铝面板
产品重量: 0.36kg

ES123LA-S/ES123LB-S



The ELEM heavy duty electric strike is suitable for cylindrical locks, Available fail safe or fail secure.

Face Plate: 165Lx43Wx32H(mm)
Voltage: 12VDC
Current: 250mA
Feature: Fail Secure ES123LA-S
Fail Secure ES123LB-S
Signal output: Locksignal NO/NC/COM
Weight: 0.36kg

重型长面板电锁口附信号输出

锁体尺寸: 长165x宽43x高32(mm)
工作电压: 12伏 (24伏可订)
适用门式: 木门、金属门
信号接点: 锁信号输出NO、NC、COM
开门方式: 单向开门
ES123LA-S 通电开门 断电关门
ES123LB-S 通电关门 断电开门
颜色选择: 不锈钢面板、铝面板
产品重量: 0.36kg

ES125/ES126



The ELEM electric strike is suitable for cylindrical locks, Available fail safe or fail secure.

Face Plate: 150Lx39.5Wx28H(mm)
Voltage: 12VDC
Current: 450mA(ES125)
200mA(ES126)
Feature: Fail Secure ES125(NO)
Fail Safe ES126(NC)
Weight: 0.36kg

标准型电锁口

锁体尺寸: 长150x宽39.5x高28(mm)
工作电压: 12伏
适用门式: 木门、金属门
开门方式: 单向开门
ES125 通电开门 断电关门
ES126 通电关门 断电开门
颜色选择: 不锈钢面板、铝面板产品
重量: 0.36kg