



ELECTROMAGNETIC LOCK SERIES

The Trusted Name For Excellent Quality



EM1200L(LED)



The ELEM Electromagnetic lock is for single door & has a holding capacity of 1200Lbs.

Lock Size: 266Lx67Wx39H(mm)
Amature Size: 185Lx60Wx15H(mm)
Voltage: Field Selectable 12V or 24VDC
Current: 420mA at 24VDC
210mA at 12VDC
Monitored with LED, NO/NC
Fail-safe type
Weight: 4.7Kg

重型单门磁力锁附信号输出

外观尺寸: 长266x宽67x高39(mm)
吸板尺寸: 长185x宽60x高15(mm)
承受拉力: 500公斤
双重电压: 12伏或24伏可选择
工作电流: 420mA/12V, 210mA/24V
信号接点: NO, NC, COM
适用门式: 木门、金属门
开门方式: 单向开门; 推或拉
通电关门、断电开门
产品重量: 4.7kg

EM1200LD(LED)



The ELEM Electromagnetic lock is for single door & has a holding capacity of 1200Lbs x 2.

Lock Size: 532Lx67Wx39H(mm)
Amature Size: 185Lx60Wx15H(mm)
Voltage: Field Selectable 12V or 24VDC
Current: 420mA at 24VDC
210mA at 12VDC
Monitored with 2LED, NO/NC
Fail-safe type
Weight: 9.4Kg

重型双门磁力锁附信号输出

外观尺寸: 长532x宽67x高39(mm)
吸板尺寸: 长185x宽60x高15(mm)
承受拉力: 500公斤x2
双重电压: 12伏或24伏可选择
工作电流: 420mA/12V, 210mA/24V
信号接点: NO, NC, COM
适用门式: 木门、金属门
开门方式: 单向开门; 推或拉
通电关门、断电开门
产品重量: 9.4kg

EM1200LT(LED)



The ELEM Electromagnetic lock is for single door & has a holding capacity of 1200Lbs.

Lock Size: 266Lx67Wx39H(mm)
Amature Size: 185Lx60Wx15H(mm)
Voltage: Field Selectable 12V or 24VDC
Current: 420mA at 24VDC
210mA at 12VDC
Time: 0.3-6.9secs
Monitored with LED, NO/NC
Fail-safe type
Weight: 4.7Kg

重型单门磁力锁附延时功能

外观尺寸: 长266x宽67x高39(mm)
吸板尺寸: 长185x宽60x高15(mm)
承受拉力: 500公斤
双重电压: 12伏或24伏可选择
工作电流: 420mA/12V, 210mA/24V
信号接点: NO, NC, COM
延时功能: 0.3-6.9
适用门式: 木门、金属门
开门方式: 单向开门; 推或拉
通电关门、断电开门
产品重量: 4.7kg

EM1200LTD(LED)



The ELEM Electromagnetic lock is for single door & has a holding capacity of 1200Lbs x 2.

Lock Size: 532Lx67Wx39H(mm)
Amature Size: 185Lx60Wx15H(mm)
Voltage: Field Selectable 12V or 24VDC
Current: 420mA at 24VDC
210mA at 12VDC
Time: 0.3-6.9secs
Monitored with 2LED, NO/NC
Fail-safe type
Weight: 9.4Kg

重型双门磁力锁附延时功能

外观尺寸: 长532x宽67x高39(mm)
吸板尺寸: 长185x宽60x高15(mm)
承受拉力: 500公斤x2
双重电压: 12伏或24伏可选择
工作电流: 420mA/12V, 210mA/24V
信号接点: NO, NC, COM
延时功能: 0.3-6.9
适用门式: 木门、金属门
开门方式: 单向开门; 推或拉
通电关门、断电开门
产品重量: 9.4kg

EM1200BZ



The ELEM Electromagnetic lock is for single door with Buzzer & has a holding capacity of 1200Lbs.

Lock Size: 266Lx67Wx39H(mm)
Amature Size: 185Lx60Wx15H(mm)
Voltage: Field Selectable 12V or 24VDC
Current: 420mA at 24VDC
210mA at 12VDC
Time: 0.3-6.9secs
Monitored with LED, NO/NC
Fail-safe type
Weight: 4.7Kg

重型单门磁力锁附报警器

外观尺寸: 长266x宽67x高39(mm)
吸板尺寸: 长185x宽60x高15(mm)
承受拉力: 500公斤
双重电压: 12伏或24伏可选择
工作电流: 420mA/12V, 210mA/24V
信号接点: NO, NC, COM
延时功能: 0-30秒可调
适用门式: 木门、金属门
开门方式: 单向开门; 推或拉
通电关门、断电开门
产品重量: 4.7kg

EM1200BZD



The ELEM Electromagnetic lock is for single door With Buzzer & has a holding capacity of 1200Lbs x 2.

Lock Size: 532Lx67Wx39H(mm)
Amature Size: 185Lx60Wx15H(mm)
Voltage: Field Selectable 12V or 24VDC
Current: 420mA at 24VDC
210mA at 12VDC
Monitored with 2LED, NO/NC
Fail-safe type
Weight: 9.4Kg

重型双门磁力锁附报警器

外观尺寸: 长532x宽67x高39(mm)
吸板尺寸: 长185x宽60x高15(mm)
承受拉力: 500公斤x2
双重电压: 12伏或24伏可选择
工作电流: 420mA/12V, 210mA/24V
信号接点: NO, NC, COM
延时功能: 0-30秒可调
适用门式: 木门、金属门
开门方式: 单向开门; 推或拉
通电关门、断电开门
产品重量: 9.4kg



ELECTRIC BOLT SERIES

The Trusted Name For Excellent Quality



EB201



The ELEM fail safe electric bolt with magnetic feature.

Face Plate: 205Lx35Wx40H(mm)
Strike: 90Lx25Wx2H(mm)
Bolt: 16mm DIA, stainless steel 16mm throw
Voltage: 12VDC
Start Current: 900mA
Stand by Current: 100mA
Fail-safe type
Weight: 0.8Kg

磁感型标准电插锁

锁体尺寸: 长205x宽35x高40(mm)
短板尺寸: 长90x宽25x高2(mm)
锁芯尺寸: 16mm(凸出长度)x16mm(直径)
工作电压: 12伏(超低功耗)
瞬间电流: 900mA
工作电流: 100mA
适用门式: 木门、玻璃门、金属门
开门方式: 双向开门; 可推拉
配备功能: 附门磁功能输出NC、COM
通电关门、断电开门
产品重量: 0.8kg

Low Temperature

EB202



The ELEM fail safe electric bolt with monitoring LED and adjustable 0-9 Seconds.

Face Plate: 205Lx35Wx40H(mm)
Strike: 90Lx25Wx2H(mm)
Bolt: 16mm DIA, stainless steel 16mm throw
Voltage: 12VDC
Operation Current: 900mA
Stand by Current: 150mA
Lock status sensor indicates door open or closed
Time: 0.2, 5.5, 9sec
Weight: 0.7Kg

磁感型安全电插锁

锁体尺寸: 长205x宽35x高40(mm)
短板尺寸: 长90x宽25x高2(mm)
锁芯尺寸: 16mm(凸出长度)x16mm(直径)
工作电压: 12伏(超低功耗)
启动电流: 900mA
工作电流: 150mA
适用门式: 木门、玻璃门、金属门
开门方式: 双向开门; 可推拉
配备功能: 附信号灯及门磁功能
延时功能: 0.2, 5.5, 9秒
通电关门、断电开门
产品重量: 0.7kg

Low Temperature

EB203



The ELEM fail safe electric bolt with magnetic feature.

Face Plate: 205Lx35Wx40H(mm)
Strike: 90Lx25Wx2H(mm)
Bolt: 16mm DIA, stainless steel 16mm throw
Voltage: 12VDC
Operation Current: 900mA
Stand by Current: 150mA
Lock when energized (power to locked fail unlocked)
Time: 0.3, 6.9 secretary
Weight: 0.8Kg

磁感型多功能电插锁

锁体尺寸: 长205x宽35x高40(mm)
短板尺寸: 长90x宽25x高2(mm)
锁芯尺寸: 16mm(凸出长度)x16mm(直径)
工作电压: 12伏(超低功耗)
启动电流: 900mA
工作电流: 150mA
适用门式: 木门、玻璃门、金属门
开门方式: 双向开门; 可推拉
配备功能: 附门磁功能及开门按钮接点
延时功能: 0.3, 6.9秒
具双电流过载保护装置
通电关门、断电开门
产品重量: 0.8kg

Low Temperature

EB204



The ELEM fail safe electric bolt is Special for Atuto-door

Face Plate: 205Lx35Wx40H(mm)
Strike: 90Lx25Wx2H(mm)
Bolt: 16mm DIA, stainless steel 16mm throw
Voltage: 12VDC
Operation Current: 900mA
Stand by Current: 280mA
Lock when energized (power to locked fail unlocked)
Time: 0.3, 6.9
Weight: 0.8Kg

自动门专用电插锁

锁体尺寸: 长205x宽35x高40(mm)
短板尺寸: 长90x宽25x高2(mm)
锁芯尺寸: 16mm(凸出长度)x16mm(直径)
工作电压: 12伏(超低功耗)
启动电流: 900mA
工作电流: 280mA
适用门式: 自动门专用
开门方式: 双向开门; 可推拉
配备功能: 附门磁功能及开门按钮接点
延时功能: 0.3, 6.9秒
具双电流过载保护装置
通电关门、断电开门
产品重量: 0.8kg

Low Temperature

EB205



The ELEM fail safe electric bolt with magnetic feature.

Face Plate: 220Lx35Wx40H(mm)
Strike: 90Lx25Wx2H(mm)
Bolt: 16mm DIA, stainless steel 16mm throw
Voltage: 12VDC
Operation Current: 950mA
Stand by Current: 150mA
Lock when energized (power to locked fail unlocked)
Time: 0.3, 6.9
Weight: 1.8Kg

重型高保安电插锁

锁体尺寸: 长220x宽35x高40(mm)
短板尺寸: 长90x宽25x高2(mm)
锁芯尺寸: 16mm(凸出长度)x16mm(直径)
工作电压: 12伏(超低功耗)
启动电流: 900mA
工作电流: 150mA
适用门式: 木门、玻璃门、金属门
开门方式: 双向开门; 可推拉
配备功能: 锁状态信号输出及自动重复功能
延时功能: 0.3, 6.9秒
承受剪力: 1000kg冲击力
通电关门、断电开门
产品重量: 1.8kg

Low Temperature